



ULTRA

ULTRA MODULAR ENTRANCE PANEL



ULTRA, the new and most technologically advanced entrance panel offering maximum ease of installation. This modular entrance panel features a modern design, created to adapt to a wide range of applications, from small to large complexes. Die-cast aluminium frames increase the entrance panel's resistance to atmospheric agents. Available in flush-mounting or surface-mounting versions (surface-mounting variant just 35 mm thick). Easy to install and configure, thanks to the smart programming of call buttons. Available in an audio and audio/video version with colour video camera. The buttons are made using professional-grade plastic given an anti-yellowing and anti-dulling treatment, or aluminium. Twilight sensor for automatic nameplate backlight switch-off during daytime hours.

AWARDS





ULTRA

ULTRA MODULAR ENTRANCE PANEL

GENERAL DATA

Type	External unit modular
Product height (mm)	315
Product width (mm)	126
Product depth (mm)	53.5
Product colour	Black RAL9005, Gray RAL 7042, Aluminum
Material	ABS, Plastic, Aluminium alloy
Flush-mounted	Yes, with a dedicated accessory
Wall-mounted	Yes, with a dedicated accessory

COMPATIBLE SYSTEMS

Audio/video Simplebus 2 with power supply art. 4888C	Yes
Audio/video Simplebus 2 with power supply art. 1210/1210A	Yes
Audio Simplebus 2 with power supply art. 1210/1210A	Yes
Audio Simplebus 1	Yes
ViP	Yes

AUDIO FEATURES

Microphone	MEMS audio digital sensor, omnidirectional
Loudspeaker	28mm (Ø), 8 Ohm, 1W (2)

CAMERA FEATURES

Camera	Colours
Sensor type	1/3" CMOS
Lens (mm)	2.8
Angle of view (H x V - °)	120 x 90
Sensitivity (lux)	0.5 (colour)

ELECTRICAL CHARACTERISTICS



ULTRA

ULTRA MODULAR ENTRANCE PANEL

Supply voltage	33VDC
----------------	-------

HARDWARE FEATURES

Call type	Push-buttons
Type of buttons	Mechanical
Backlight colour	White, Off
Communication ports	Micro-USB
Twilight sensor	Yes

SETTINGS

Loudspeaker volume	Yes
Microphone volume	Yes

ENVIRONMENTAL AND COMPLIANCE FEATURES

IP protection degree	IP65
IK vandal-proof protection degree	IK08
Operating temperature (°C)	-25 ÷ 55
Operating humidity (RH max - %) (%)	25 ÷ 95
Environmental class	IV
Compliance and Certifications	RoHS II - 2011/65/UE (EN 50581:2012), EMC 2014/30/UE (EN 61000-6-1:2007 , EN 61000-6-3:2007+A1:2011)

MAIN FUNCTIONS

Door opener	Yes
Input for local door release button	Yes
Door open signaling input	Yes
Visual indications of system status	Yes